



GENERAL CARE AND CLEANING GUIDE FOR VINYL COATED FABRICS

Step #1: Most common everyday light soiling can be easily removed by using a solution of 10% liquid household dish soap and 90% warm water, applied with a clean dampened cloth. Rinse with a clean cloth dampened with water and allow to dry. Moderate scrubbing with a soft bristle brush will help loosen dirt and grime embedded in the grain of the vinyl.

Step #2: For more stubborn stains and heavy soiling dampen a soft white cloth with CMI V-Clean r, Formula 409 r, or Fantastik r. Rub gently and rinse with a soft cloth and clean water.

Step #3: For the most difficult stains and surface mildew dampen a clean white cloth with a solution of 10% household bleach and 90% water. Rub gently and rinse with a clean water dampened cloth.

This information is a guideline and not a guarantee and does not relieve the user from the responsibility of proper care, cleaning, and use of the Product and all cleaning agents. The use of certain cleaning agents, including but not limited to powdered abrasives, solvents, industrial strength cleaners and power washing is not recommended and can be harmful to the surface appearance and the lifespan of the Product. The Supplier, its agents and assigns assume no responsibility resulting from the use of such cleaning agents or procedures to the vinyl and use of such will void the warranty.

V-Clean is a registered trademark of CMI Enterprises, Inc. Formula 409 is a registered trademark of the Clorox Company. Fantastik is a registered trademark of The Dow Chemical Company.